

### Rotary Driver for Swing Gate & Folding Gate



Infrared Safety Device (optional)

Stronger, extra power inside the GFM-925W

30% extra power compare to other non-monoblock models



#### Monoblock Cast Aluminium Design

The main gearbox consist of multiple stages planetary gear system, built from single block of aluminium, ensuring maximum toughness



The solution to oversized folding gate

#### TECHNICAL SPECIFICATIONS

- Electric motor - DC 12V
- Main power supply - AC 230V (Hybrid Model)
- DC 20V (Solar Model)
- DC 12V 7AH
- Backup battery - 4 stages planetary type
- Reduction gear - 2000kg-cm
- Output torque (Dynamic) - 3240kg-cm
- Output torque (Static) - 1.8 r.p.m.
- Output speed (At full speed)

## ADVANCE FUNCTIONS

Anti-Spy Encryption Tech



Wireless Multi Function Keypad



Infrared Safety Device (optional)

To stop or reverse the gate if it detects an obstruction along the passage



#### Automatic Close Timer

Using the keypad to preset a timer to close the gate if it is left open after the preset time

(must work with infrared safety device)



#### Motion Lock

Using the keypad to inhibit the gate from opening or closing



#### Panic Alarm

Panic alarm can be triggered via the remote control or the keypad in case of an emergency



#### Intruder Alarm

The function is armed via the keypad. Intrusion detected by the infrared safety device will trigger the alarm

(must work with infrared safety device)

## THE WIRELESS ADVANTAGE

The multi function keypad is wireless. Therefore you can place it anywhere you like



Dealer:

Some graphics are artist impressions and may differ from the actual appearance

In some countries, installing the infrared safety device is compulsory by law of the local authority

Depending on the sales and purchase agreement with your dealer, or due to some on-site constraints, some features may be not available

*\*Specifications may vary and are subject to change without prior notice*