

# KEEPSAFER®

## WIRELESS HOME SECURITY



# VALUE PRICED SECURITY SYSTEM FOR ANY SIZE HOME

Central Station Monitoring Available  
for Round-the-Clock Protection



- Full-featured, professional quality security system
- Proven deterrent to intruders
- Protection for doors, windows, sliding glass doors, gun cabinets, and interior areas
- Optional keychain remote control
- Expandable to meet your security needs
- Many homeowner's insurers offer policy discounts for home security systems

### The SSD-8 security system offers:

- Portable console for wall mounting or tabletop use, packaged with 2 door/window sensors for protecting entry points
- System support for up to 8 wireless SSD sensors
- 4 modes of easy operation (HOME, AWAY, CHIME, and OFF)
- Operation from any electrical outlet—continuous protection even in a power failure with the addition of back-up batteries (two 9V alkaline, not supplied)
- Loud internal alarm siren, plus unique tones for button presses, mode changes, chimes, and entrance/exit delays
- Comprehensive, easy-to-follow owner's manual



**EASY TO INSTALL.  
NO TOOLS REQUIRED.**

## SSD-8 System Specifications

Frequency: 315 MHz

Range: 275 feet, typical

Transformer: 12 Vdc

**Current consumption:** 50 mA maximum standby;  
300 mA maximum with siren on

**Modes:** OFF, CHIME, HOME, and AWAY (green LED)

**Security zones:** exterior, interior, emergency

**Entry/exit delay:** 45 seconds

**Alarm cutoff:** 255 seconds

**Alarm memory:** all alarming channels, cleared at next  
mode change

**Transmitter zone displays:** 8 (red LED)

**Audio/siren:** internal speaker provided, 2 watts max.

**Volume control:** internal adjustment

**Transmitter compatibility:** door/window sensor,  
keychain transmitter, motion detector

**Transmitters learned:** 8 maximum

**Arm/disarm code:** single 1 to 5 digit code

**Mounting:** wall mount or table top (wall mount bracket and  
rubber feet included)

**Temperature range:** 0 to 50°C

### SYSTEM OPTIONS

- a. **External speaker:** 8 ohms nominal, 2 watts; reduces  
internal speaker volume
- b. **Battery backup:** two 9V alkaline batteries (not supplied);  
24 hours minimum standby with 2 siren cycles
- c. **24-hour central station monitoring:** requires telephone  
dialer/communicator
- d. **Voice dialer:** in an alarm, automatically calls emergency  
telephone numbers programmed by user

### PACKAGE

**Dimensions:** 11-9/16 inches W x 10 inches H x 4-1/16  
inches D

### AVAILABLE ACCESSORIES

- a. Additional door/window sensors
- b. Glass break detector
- c. Magnetic contact set
- d. Passive infrared motion detector
- e. Two-button keychain remote control
- f. External siren
- g. Yard sign

**KEEPSAFER<sup>®</sup>**  
**BY Linear.**

LINEAR CORPORATION  
2055 Corte Del Nogal  
Carlsbad, CA 92009  
(800) 421-1587